

CAMBRIDGE INTERNATIONAL EXAMINATIONS
Cambridge International Advanced Subsidiary and Advanced Level

MARK SCHEME for the May/June 2015 series

9691 COMPUTING	
9691/22	Paper 2 (Written Paper), maximum raw mark 75

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge will not enter into discussions about these mark schemes.

Cambridge is publishing the mark schemes for the May/June 2015 series for most Cambridge IGCSE[®], Cambridge International A and AS Level components and some Cambridge O Level components.

1 (a) (i) 'F'

(ii) Error

(b) ThisDay ← MID(TodaysDate, 1, 2)
ThisMonth ← MID(TodaysDate, 3, 2)
ThisYear ← MID(TodaysDate, 5, 4)

[3]

2 (a) (i)

x	Result	x < > -1
0	0	TRUE
3	3	TRUE
5	8	TRUE
2	10	TRUE
1	11	TRUE
-1	10	FALSE

1 mark per correct column [3]

OUTPUT: 10 [1]

(ii) Expected result: 11 [1]

(iii) The -1 is treated as though it was part of the sequence of numbers // the dummy value is included in the calculation [1]

(iv) Logic (error) (Accept logical) [1]

Page 3	Mark Scheme	System Paper
	Cambridge International AS/A Level – May/June 2015	969

```
(b) DECLARE x : INTEGER
    DECLARE Result : INTEGER
    * ← ← ←
    Result ← 0
    INPUT x
    WHILE x <> -1
    Result ← Result + x
    INPUT x
    ENDWHILE
    OUTPUT Result
```

- Mark as follows:
- If no change attempted – no marks
 - If a change has been attempted:
 - Correct declarations and output statements 1 mark
 - Moving INPUT x within the loop to the end of the loop 1 mark
 - Or IF x <> -1 THEN 1 mark
 - If loop works and Initialisations correct 1 mark
- [3]**

3 (a) (i) Row 2 [1]
 Column 3

(ii) NULL / "" (empty string)/ any char other than '0', 'O' or 'X' [1]

- (iii) Mark as follows:
- Correct identifier
 - Correct dimensions
 - Correct data type in declaration (Correct for initial value used below)
 - Correct outer loop
 - Correct inner loop
 - Correct indices for assignment (LH)
 - Assign initial value within loop (RH) if not a valid initial value

Example Pascal

```
VAR Grid : ARRAY [1..3, 1..3] OF CHAR;
FOR Row := 1 TO 3 DO
    FOR Column := 1 TO 3 DO
        Grid[Row, Column] := NULL;
```

[7]

- (b) (i) *Invalid with correct reason 1 mark each*
- 2,2: valid 1 mark
 - 0,1: invalid because row below range 1 mark
 - 1,1: valid 1 mark for the two valid cases
 - 1,4: column above range 1 mark
 - 4,1: row above range 1 mark
 - 2,0: Column below range 1 mark
 - 2,2: Cell already used (row & column within range) 1 mark

[6]

Page 4	Mark Scheme	System Paper
	Cambridge International AS/A Level – May/June 2015	969

- (ii) **Mark as follows:**
- Correct function identifier and ending
 - Function parameter and return data type
 - Check row within range AND
 - Check column within range
 - Check cell is empty (requires correct logical structure)
 - Correct return values (accept TRUE/FALSE as strings)

Example Pascal

```
FUNCTION IsInputValid (Row, Column : INTEGER) : BOOLEAN;  
  VAR IsValid : BOOLEAN;  
  BEGIN  
    IsValid := FALSE;  
    IF (Row>0) AND (Row<4)  
      THEN  
        IF (Column>0) AND (Column<4)  
          THEN  
            IF Grid[Row, Column] = NULL // or equivalent  
              THEN IsValid := TRUE;  
    IsValid := IsValid  
  END;
```

[max 5]

- (c) (i) Use of functions/procedures [1]
- (ii) Easier to solve (by breaking down into sub-problems)
Can focus on one part at a time
easier to produce module code [1]
- (iii) Assignment: 1 / 2 / 10 / 15
Selection: 8(-20) / 13(-19)
Iteration: 5(-21) / 21
Function call: 8 / 13
Procedure call: 3 / 6 / 7 / 18 [5]
- (iv)
 - indentation
 - meaningful identifier/variable names
 - keywords in capitals
 - inclusion of white space
 - initialising variables
 - one statement per line
 - use of functions/procedures with meaningful identifiers // use of structured constructs

[max 2]

(v)

Identifier	Variable or Procedure or Function or Array	Data Type	Description
GameEnd	Variable	BOOLEAN	FALSE if game in progress TRUE if there is a winner or the grid is full
Grid	ARRAY	CHAR character STRING(1)	To store the current state of the game
CurrentPlayer	Variable	CHAR character STRING(1)	The marker value ('O' or 'X') of the current player
PlayerTakesTurn	PROCEDURE	(ignore)	Current player chooses cell Program checks if it is valid and stores marker
DisplayGrid	PROCEDURE	(ignore)	Outputs the contents of the grid
HasPlayerWon	FUNCTION	BOOLEAN	Checks if the current player has completed a row, column or diagonal
GridFull	FUNCTION	BOOLEAN	Checks if the grid is full
SwapPlayer	PROCEDURE	(ignore)	Swaps the value of CurrentPlayer

[5]

(d) Mark as follows:

- Procedure heading and ending
- parameter given
- Byref (parameter)
- Parameter data type as CHAR (accept string)
- IF 'O' then 'X'
- IF 'X' then 'O'

```
PROCEDURE SwapPlayer (BYREF Player : CHAR)
  IF Player = 'O'
    THEN Player ← 'X'
    ELSE Player ← 'O'
  ENDIF
ENDPROCEDURE
```

[max 5]

Page 6	Mark Scheme	Syllabus Paper
	Cambridge International AS/A Level – May/June 2015	969

(e) FUNCTION HasPlayerWon() RETURNS BOOLEAN accept AS or : or just BOOLEAN

```

DECLARE WinningLine : BOOLEAN
DECLARE i : INTEGER
WinningLine ← FALSE
    // check both diagonals
IF    Grid[1,1] = Grid[2,2] AND Grid[1,1] = Grid[3,3]
    OR Grid[1,3] = Grid[2,2]
    AND Grid[1,3] = Grid[3,1]
THEN WinningLine ← TRUE
ELSE
    i ← 0
    REPEAT accept LOOP / DO // DO LOOP
    i ← i + 1
    // check a row
    IF    Grid[i,1] = Grid[i,2] AND Grid[i,1] =
    // check a column
    OR Grid[1,i] = Grid[2,i]
    AND Grid[1,i] = Grid[3,i]
    THEN WinningLine ← TRUE
    ENDIF
UNTIL WinningLine = TRUE OR i=3
ENDIF
RETURN WinningLine
ENDFUNCTION

```

1 mark

Ensure the following elements have been checked:
Grid[1,3]
Grid[3,1]
Grid[2,2]
Grid[3,1] =

1 mark

Ensure the following elements have been checked:
Grid[1,i]
Grid[2,i]
Grid[3,i]
Grid[3,1] =

[max 10]

Page 7	Mark Scheme	System Paper
	Cambridge International AS/A Level – May/June 2015	969

(f) Example Pascal:

```
PROCEDURE DisplayGrid;
BEGIN
  EmptyCell:= '' // value for empty cell see 3(a)(ii)
  FOR Row := 1 TO 3 DO
  BEGIN
    Line := ''; // build up a row for output
    FOR Column := 1 TO 3 DO
      IF Grid[Row, Column] = EmptyCell
      THEN
        Line := Line + ' : '
      ELSE
        Line := Line + ' ' + Grid[Row, Column] + ' ';
      WriteLn(Line);
    END;
  END;
END;
```

Mark as follows:

- Procedure header & ending
- Assign empty cell value to EmptyCell
- Correctly nested loops
- Correct Boolean expression in IF statement
- Correct string concatenation × 2
- Initialise line and output line

[max 5]

(g) Mark as follows:

- Display of 3×3 grid to represent the current state of the game
- Input box/ drop-down box for row number clearly labelled (Accept radio buttons)
- Input box/ drop-down box for column number clearly labelled (Accept radio buttons)
- Indication of which player's turn (Do not accept radio buttons / check boxes)
- Error message if invalid input

[max 4]

(h) Any **two** from:

- System testing
- Integration testing
- Black box testing
- White box testing // glass box testing

[max 2]